



0.875 Inch | 22.225 Millimeter x 1.219 Inch |
30.963 Millimeter x 1.438 Inch | 36.525 Millimeter
TIMKEN VAS 7/8 Pillow Block Bearings

Bearing No. VAS 7/8

VAS 7/8 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	0.76
EAN	0087796056985
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	GRA013RRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row Spherical Normal Duty High Base With Set Screw
Long Description	2 Bolt Pillow Block; 7/8" Bore; 1-7/16" Base to Center Height; Eccentric Collar



Tianjin Samy Bearing Technology Co., ...

	Mount; Ball Bearing; Relubricatable; Cast Iron; Double Land Riding Rubber Contact; Non- expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	VAS 7/8
Weight / LBS	1.67
D	1.219 Inch 30.963 Millimeter
B	1.438 Inch 36.525 Millimeter
Bolt Spacing Minimum	0 Inch 0Millimeter
d	0.875 Inch 22.225 Millimeter
Actual Bolt Center to Center	4.1 Inch 105Millimeter
Nominal Bolt Center to Center	4.1 Inch 105 Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Shaft Size d	7/8 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.531 in
Dimension T	0.705 in
Series	Standard
Weight	1.671 lb
Seal Type	Molded Shroud
Base to Center Height H	36.51 mm
Total Length L	139.70 mm



Tianjin Samy Bearing Technology Co., ...

Total Width A	1.406 in
Bolt Hole Spacing J	104.8 mm
Bolt Hole Width N	11.1 mm
Bolt Hole Length N1	20.6 mm
Foot Height H1	15.1 mm
Total Height H2	71.4 mm
Dimension L1	46.6 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	7.6 mm
Dimension B1	1.220 in
Static Load Rating	1750 lbf
Dynamic Load Rating	3490 lbf